



FRONT ELEVATION

SCALE: $\frac{3}{8}$ "=1'-0"

SECTION

SCALE: $\frac{3}{8}$ "=1'-0"

GENERAL NOTES:

1. THIS DRAWING SHOWS THE GENERAL SHAPE AND APPROXIMATE PROFILE OF THE ADIT AT THE INTENDED LOCATION OF THE CLOSURE. FIELD VERIFY DIMENSIONS PRIOR TO FABRICATION.
2. TUBULAR STEEL, STEEL PLATES, AND SHAPES SHALL BE WEATHERING STEEL AS SPECIFIED. WELD ALL JOINTS. JOINTS SHALL BE TIGHT SO THAT MOISTURE CANNOT ENTER BETWEEN PILES OF MATERIAL. ROUND OR CHAMFER ALL SHARP EDGES AND CORNERS.
3. PRIOR TO CONSTRUCTING THE FOOTER, REMOVE RUBBLE TO THE LEVEL INDICATED AND AS DIRECTED BY THE ON-SITE AML REPRESENTATIVE. FOOTER BASE SHALL BE LEVEL AND WELL COMPACTED TO THE SATISFACTION OF THE AML PROJECT MANAGER.
4. GROUT SHALL BE CONSTRUCTION GRADE.
5. PLACE A $\frac{3}{8}$ " CHAMFER ON ALL EXPOSED EDGES OF CONCRETE FOOTER.
6. TOLERANCES ON THE CENTER-TO-CENTER DIMENSIONS BETWEEN POSTS SHALL BE $\pm\frac{1}{16}$ ".
7. PLACE A SURVEY MARKER, PROVIDED BY THE PROJECT MANAGER, INTO THE GROUTED LINE.

CAUTION - THIS PROJECT REQUIRES CONSTRUCTION WORK IN, AROUND, AND OVER HAZARDOUS AND UNPROTECTED MINE SHAFTS, STOPS, ADITS AND OTHER OPENINGS WHICH MAY BE UNSTABLE. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THOROUGHLY INVESTIGATING THE SITE CONDITIONS AND SCHEDULING EQUIPMENT, EQUIPMENT OPERATORS, OPERATIONS, PERSONNEL AND SAFETY PROCEDURES TO PREVENT ACCIDENTS AND INJURIES.

ABANDONED MINE LAND PROGRAM
MINING AND MINERALS DIVISION
ENERGY, MINERALS AND NATURAL RESOURCES DEPARTMENT

SCALE: AS SHOWN
DATE: SEPT. 29, 2010
DRAWN BY: JTG
REVISED:

FEATURE 11 ADIT

Harding Pegmatite Mine Safeguard Project
DRAWING NUMBER
FIGURE 19