


CAUTION - THIS PROJECT REQUIRES CONSTRUCTION WORK IN, AROUND, AND OVER HAZARDOUS AND UNPROTECTED MINE SHAFTS, STOPES, ADITS, HIGHWALLS AND OTHER FEATURES WHICH MAY BE UNSTABLE. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THOROUGHLY INVESTIGATING THE SITE CONDITIONS AND SCHEDULING EQUIPMENT, EQUIPMENT OPERATORS, OPERATIONS, PERSONNEL AND SAFETY PROCEDURES TO PREVENT ACCIDENTS AND INJURIES.



FRONT ELEVATION

SCALE: $\frac{3}{4}$ "=1'-0"

SECTION

SCALE: $\frac{3}{4}$ "=1'-0"

GENERAL NOTES:

1. THIS DRAWING SHOWS THE GENERAL SHAPE AND APPROXIMATE PROFILE OF THE ADIT AT THE INTENDED LOCATION OF THE CLOSURE. USE THE DRAWING AS A GUIDE FOR FIELD LAYOUT OF THE CLOSURE. FIELD VERIFY DIMENSIONS PRIOR TO FABRICATION.
2. TUBULAR STEEL, STEEL PLATES, AND SHAPES SHALL BE WEATHERING STEEL AS SPECIFIED. WELD ALL JOINTS. JOINTS SHALL BE TIGHT SO THAT MOISTURE CANNOT ENTER BETWEEN PLIES OF MATERIAL. ROUND OR CHAMFER ALL SHARP EDGES AND CORNERS.
3. PRIOR TO CONSTRUCTING THE FOOTER, REMOVE RUBBLE AND LEVEL THE FLOOR IN THE AREA OF THE CLOSURE AS DIRECTED BY THE ON-SITE AML REPRESENTATIVE.
4. GROUT SHALL BE CONSTRUCTION GRADE.
5. PLACE A $\frac{3}{4}$ " CHAMFER ON ALL EXPOSED EDGES OF CONCRETE FOOTER.
6. TOLERANCES ON THE CENTER-TO-CENTER DIMENSIONS BETWEEN POSTS SHALL BE $\pm \frac{1}{16}$ ".
7. PLACE A SURVEY MARKER, PROVIDED BY THE PROJECT MANAGER, INTO THE GROUTED LINTEL.

ABANDONED MINE LAND PROGRAM MINING AND MINERALS DIVISION ENERGY, MINERALS AND NATURAL RESOURCES DEPARTMENT		
SCALE: AS SHOWN		DRAWN BY: JTG
DATE: AUG. 24, 2010		REVISED:
FEATURE 17 ADIT		
Harding Pegmatite Mine Safeguard Project		DRAWING NUMBER: FIGURE 20